MOL DSG / DCT Fluid

dual-clutch gearbox oil

MOL DSG / DCT Fluid is an unique gearbox oil produced from severely hydrocracked, high quality base oils, using a special additive system that meets the highest quality requirements. Provides excellent wear protection as well as outstanding wet clutch performance.

Application



Dual-clutch transmissions of passenger cars and light commercial vehicles

Features and benefits

Optimal friction characteristics	Wet clutches operate silently and judder-free
Excellent cold flow properties	Fuel-saving operation at low temperature
Low foaming tendency	Continuous, stable lubricating film, even at high speeds
Excellent wear protection	Long gear lifetime, giving reliable operation
Exceptional thermal and oxidation stability	Perfect protection against sludge formation and sedimentation

Specifications and approvals

VW G 052 182 (TL 52 182)
VW G 052 529 (TL 52 529)
BMW 83 22 0 440 214
BMW 83 22 2 147 477
BMW 83 22 2 148 578
BMW 83 22 2 148 579
Ford M2C936A
MZ320065 Dia-Queen SSTF-I
PSA 9734.S2
Porsche Oil No. 999.917.080.00
Volvo 1161838/1161839
Nissan 999MP-GTRT00P
VW G 055 529

Properties

Properties	Typical values
Appearance	yellow, clear, bright
Density at 15°C [g/cm3]	0,854
Kinematic viscosity at 40°C [mm2/s]	34,3
Kinematic viscosity at 100 °C [mm2/s]	7,20
Pour point [°C]	-42
Flash point (Cleveland) [°C]	200

The characteristics in table are typical values of the product and do not constitute a specification.

Manufactured and distributed by MOL-LUB Ltd., 2931 Almásfüzitő, Fő út 21.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service:
Tel: +36 (1) 886-5030 (option 2); E-mail: lubtechdesk@mol.hu

MOL DSG / DCT Fluid

dual-clutch gearbox oil

Storage and handling instructions

Store in the original container in dry, properly ventilated area.
Keep away from direct flame and other sources of ignition.
Protect from direct sunlight.
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.
For further details please read the Material Safety Data Sheet of the product.
Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.
The manufacturer and distributor shall not be held liable for such possible damages.
In the original container under the recommended storage conditions: 60 months
Recommended storage temperature: +5°C - +40°C