
MOL Hykomol 90

automotive gear oil

MOL Hykomol 90 is a monograde gear oil composed of highly refined base oils using additives having combined effects.

Application



	Manual and automatic mechanical gearboxes of commerical vehicles
	Manual gearboxes of passenger cars and light commercial vehicles
	Oil lubricated rolling bearings
	Manual gearboxes, gear drives of agricultural and construction machines

Features and benefits

Excellent wear protection	Long gear lifetime, giving reliable operation
Up-to-date additive system	Efficient EP performance, giving a long life for synchronizing rings
Low foaming tendency	Stable, continuous lubricating film, giving reduced wear
Good thermal and oxidation stability	Excellent properties are sustained for a long time
Outstanding corrosion protection	Long-term protection of parts

Specifications and approvals

Viscosity grade: SAE 90
API GL-4
MIL-L-2105

Properties

Properties	Typical values
Density at 15°C [g/cm3]	0,894
Kinematic viscosity at 40°C [mm2/s]	165
Kinematic viscosity at 100 °C [mm2/s]	15,4
Viscosity index	85
Pour point [°C]	-24
Flash point (Cleveland) [°C]	240

The characteristics in table are typical values of the product and do not constitute a specification.

Manufactured and distributed by MOL-LUB Ltd., 2931 Almásfüzitő, Fő út 21.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service:
Tel: +36 (1) 886-5030 (option 2); E-mail: lubtechdesk@mol.hu

MOL Hykomol 90
automotive gear oil

Storage and handling instructions

Store in the original container in dry, properly ventilated area.
Keep away from direct flame and other sources of ignition.
Protect from direct sunlight.
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.
For further details please read the Material Safety Data Sheet of the product.
Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.
The manufacturer and distributor shall not be held liable for such possible damages.
In the original container under the recommended storage conditions: 60 months
Recommended storage temperature: max. 40°C