MOL ATF 3H AP

automatic transmission fluid

MOL ATF 3H AP is an automatic transmission fluid produced from synthetic and refined mineral base oils made by unique oil refining processes and using a complex additive system. This product was specifically formulated to meet the needs of Japanese and Korean passenger cars.

Application



	Automatic transmissions in modern passenger cars, SUVs and light commercial vehicles
	Hydraulic servo equipment

Features and benefits

Excellent wear protection	Long gear lifetime, giving reliable operation
Exceptional thermal and oxidation stability	Longer lubricant lifetime,so reduced operational costs
Optimal friction characteristics	Precise and noiseless switching between gears Convenient and economical operation
Excellent shear stability	Maintains its favourable properties for a long period even under heavy loads and shear stresses
High viscosity index	Optimum lubrication and reliable operation in a wide range of environmental and operational temperatures
Excellent cold flow properties	Fuel-saving operation at low temperature Reliable start-up, even in extreme cold conditions

Manufactured and distributed by MOL-LUB Ltd., 2931 Almásfüzitő, Fő út 21.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service:
Tel: +36 (1) 886-5030 (option 2); E-mail: lubtechdesk@mol.hu

MOL ATF 3H AP

automatic transmission fluid

Specifications and approvals

GM Dexron-IIIH
JASO M315 1A
Ford Mercon
MAN 339 Typ Z1
Volvo 97340
Toyota T-III
Toyota T-IV
Toyota Type D-2
Toyota WS
Mazda ATF D-III
Mazda ATF M-3
Suzuki ATF Oil
Suzuki ATF Oil Special
Subaru ATF
Nissan Matic-D
Nissan Matic-J
Mitsubishi Diamond SP-II
Mitsubishi Diamond SP-III
Kia
Hyundai
ZF TE-ML 14A
Voith H55.6335
Allison C-4
JWS 3309 (JWS 3317 till 2006)

Properties

Properties	Typical values
Density at 15°C [g/cm3]	0,851
Kinematic viscosity at 40°C [mm2/s]	36,8
Kinematic viscosity at 100 °C [mm2/s]	7,2
Viscosity index	165
Pour point [°C]	-52
Flash point (Cleveland) [°C]	215

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.
Keep away from direct flame and other sources of ignition.
Protect from direct sunlight.
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.
For further details please read the Material Safety Data Sheet of the product.
Gear oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.
The manufacturer and distributor shall not be held liable for such possible damages.
In the original container under the recommended storage conditions: 60 months
Recommended storage temperature: max. 40°C