MOL Essence SL 10W-40

semi-synthetic motor oil

MOL Essence SL 10W-40 is a state-of-art product made from a high performance synthetic base oil and premium quality mineral base oils that provide triple antioxidant protection, using a complex additive system, developed for passenger cars and commercial vehicles.

Application



	Naturally aspirated or turbocharged, gasoline and diesel engines in passanger cars and light commercial vehicles (<3.5 t weight)
	Naturally aspirated, turbocharged and direct injection diesel engines

Features and benefits

Triple antioxidant protection	Prevents presence of free radicals responsible for oil ageing, through triple anti-oxidant action, increasing the service life of the motor oil and the engine
Excellent shear stability	Preserves viscosity properties during the entire oil change period
Low volatility	Lowers engine oil consumption and reduces the emission of harmful substances Economical operation

Specifications and approvals

	Viscosity grade: SAE 10W-40 API SL/CF

Properties

Properties	Typical values
Appearance	bright, clear
Density at 15 °C [g/cm3]	0,869
Kinematic viscosity at 100 °C [mm2/s]	13,55
Apparent viscosity (CCS) at -25°C [mPa.s]	6061
Pour point [°C]	-36

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

In the original container under the recommended storage conditions: 60 months
Recommended storage temperature: max. 40°C

Manufactured and distributed by MOL-LUB Ltd.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service: H-1117 Budapest, Neumann János u. 1/E.
Tel: + 36 (1) 464-02-36 E-mail: lubtechdesk@mol.hu

MOL Essence SL 10W-40
semi-synthetic motor oil

Ordering information

Custom Tariff Number 27101981

SAP code and packaging:

13302566	MOL Essence SL 10W-40 4L	4 l plastic can (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.

Manufactured and distributed by MOL-LUB Ltd.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service: H-1117 Budapest, Neumann János u. 1/E.
Tel: + 36 (1) 464-02-36 E-mail: lubtechdesk@mol.hu